

RTT

Round Taper Tool

- Unique spring loaded split jaw design allows **FAST & EASY insertion, compression and removal** of cable assembly
- Tool designed to be used with the following 360° Radial Compression Connectors:
 - Antec - Digicon™ Series 6 & 59
- Toggle action allows minimal hand force and maximum strength to complete connector assembly
- Rugged, steel "O" Frame design with heat treated components, assures long operating life
- Unique adjustment features provide cable connector assembly reliability
- Full Cycle ratchet mechanism, with easy access escape lever, assures a complete assembly each and every time
- Improved HIGH VISIBILITY yellow cushion grips provide more comfort and like our original design will not rotate or slip during use
- Made in the U.S.A., U.S. Patent No.: 5,392,508; 5,596,800; 5,743,131; & 6,112,404
- Length: 11.50 in (292 mm) • Weight: 2.06 lbs (917 g)



TW Torque Wrenches

All our quality torque wrenches share many of the same features including...

- Prevent damage to equipment from over or under tightening
- Proper connectorization at "F" connector interface with factory preset torque setting
- Audible "clicking" sound to indicate proper calibrated torque
- High visibility yellow cushion grip body
- Model number, torque inch-pounds and wrench size stamped on tool for easy identification
- Available in multiple torque (inch-pound) settings and wrench sizes (see models below)
- Length: 6.50 in (165 mm)
- Weight: 6.5 oz (182 g)

TW

- Available in a range of **straight head** sizes
- **Tap port re-threader** on end of tool body
- Handy, removable belt loop



Torque in inch-pounds	Torque in Newton Meters	Wrench Sizes & TW Model Numbers			
		*7/16 inch (11.1 mm)	1/2 inch (12.7 mm)	9/16 inch (14.3 mm)	5/8 inch (15.9 mm)
20	2.26	TW 207	-	-	-
30	3.39	TW 307	TW 308	TW 309	TW 3010
40	4.51	TW 407	TW 408	TW 409	TW 4010

* 7/16 in for universal "F" connectors

TW-AH-B

- Basic **Angled head** model



Torque in inch-pounds	Torque in Newton Meters	Wrench Size Model Number
20	2.26	All wrenches 7/16 inch (11.1 mm)
30	3.39	TW 207-AH-B
40	4.51	TW 307-AH-B TW 407-AH-B

TW-AH-S

- **"Speed"** head allows fast tightening without removing wrench from connector
- **Note:** Wrench works in tightening mode only.



Torque in inch-pounds	Torque in Newton Meters	Wrench Size Model Number
20	2.26	All wrenches 7/16 inch (11.1 mm)
30	3.39	TW 207-AH-S TW 307-AH-S

TW-AH-516

- **Angled head** for easy access
- **5/16" socket** on the end of tool body for tightening of tap faceplates



Torque in inch-pounds	Torque in Newton Meters	Wrench Size Model Number
20	2.26	All wrenches 7/16 inch (11.1 mm)
30	3.39	TW 207-AH-516
40	4.51	TW 307-AH-516 TW 407-AH-516

TW-AH

- **Angled head** for easy access
- **Tap port rethreader** on end of tool body
- Handy, removable belt loop



Torque in inch-pounds	Torque in Newton Meters	Wrench Size Model Number
20	2.26	All wrenches 7/16 inch (11.1 mm)
30	3.39	TW 207-AH
40	4.51	TW 307-AH TW 407-AH

TW-AH/IT

- **Angle head** design
- **Connector insertion tool** on body for fast and easy "F" connector insertions
- Handy removable belt loop



Torque in inch-pounds	Torque in Newton Meters	Wrench Size Model Number
20	2.26	All wrenches 7/16 inch (11.1 mm)
25	2.83	TW 257-AH/IT
30	3.39	TW 307-AH/IT
40	4.51	TW 407-AH/IT